


## WS10 WATER SUCTION AND DELIVERY HOSE



RECOMMENDED FOR MEDIUM TO LIGHT DUTY WATER SUCTION AND DELIVERY FOR AGRICULTURAL, CONSTRUCTION AND INDUSTRIAL.



- Tube** : Black, smooth rubber compound
- Reinforcement** : Synthetic, high tensile strength textile with embedded helix wires.
- Cover** : Black wrapped finish. Resistant to weather and abrasion.
- Temperature** : -20°C to + 80°C
- Branding** :  WS10-(size) WATER SUCTION/DELIVERY HOSE ID (size) W.P. 150PSI B.P. 450PSI
- Brand Type** : Blue negative branding on black cover.

PRODUCT CODE	I. D.		O. D.		W. P.	B. P. THEORETICAL
	(IN)	(MM)	(IN)	(MM)	(PSI)	(PSI)
<b>WS10-16</b>	1	25	1.378	35	150	450
<b>WS10-20</b>	1 <sup>1</sup> / <sub>4</sub>	32	1.654	42	150	450
<b>WS10-24</b>	1 <sup>1</sup> / <sub>2</sub>	38	1.929	49	150	450
<b>WS10-32</b>	2	51	2.480	63	150	450
<b>WS10-40</b>	2 <sup>1</sup> / <sub>2</sub>	63	2.992	76	150	450
<b>WS10-48</b>	3	76	3.543	90	150	450
<b>WS10-56</b>	3 <sup>1</sup> / <sub>2</sub>	90	4.094	104	150	450
<b>WS10-64</b>	4	102	4.646	118	150	450
<b>WS10-80</b>	5	127	5.709	145	150	450
<b>WS10-96</b>	6	152	6.811	173	150	450
<b>WS10-128</b>	8	203	8.976	228	150	450

\* Other sizes are available on request.

Due to continual product improvements, UNI-FLEX™ reserves the right to alter specs without prior notice.